

# EVD-150D








DC Charging Station



## LEADING - EDGE TECHNOLOGY

Large capacity DC charger for public charging station, dual CCS plug

### Features

-  Programmable charging mode
-  7 inch touch screen
-  Comprehensive protection
-  European Standard
-  Multiple communication modes
-  Dual output ports
-  Hidden design, anti-theft

**Shenzhen Ateess Power Technology Co.,Ltd**

1st Floor of Building 3 at Sector B and 3rd Floor of Building 9,Henglong Industrial Park, No.4 Industrial Zone, Shuitian Community, Shiyan Street, Baoan District, Shenzhen

# Datasheet

## EVD-150D

### Input & Output

Input voltage	340~460V AC
Rated input voltage	400V AC
Frequency	50Hz±1
DC plug type	CCS Type 2,double plugs
Output voltage range	200~850V DC
Max. output power	150kW
Max. output current	Single connector MAX:200A
Voltage accuracy	±0.5%
Current accuracy	≥30A:≤±1% ; <30A:≤±0.3A
Voltage-regulating accuracy	±0.5%
Current-regulating accuracy	≤±1%
Ripple coefficient	RMS: ≤±0.5%; Peak: ≤±1%
Metering accuracy	0.5%
Efficiency	≥94%
Cable Length	5m

### Protection

Over voltage protection	Yes
Under voltage protection	Yes
Over load protection	Yes
Leakage current protection	Yes
Over-temp protection	Yes
Short circuit protection	Yes
Lightning protection	Yes

### Function & Accessory

Display	7 inch touch screen
Ethernet/WIFI/4G	Yes/Yes/Opt
Charging mode	APP/RFID/Plug and Charge
Indicator	Yes
Emergency stop	Yes

### Working Environment

Protection degree	IP54
Operating temperature	-25°C ~+50°C
Relative humidity	5%-95% non-condensing
Maximum altitude	2000m
Cooling	Forced air cooling
Standby power consumption	<30W
Noise emission	≤65db

### Mechanical

Dimension (W/H/D)	1270/2110/910mm
Weight	800kg

### Certificate

Certificate	CE
-------------	----